# Data sheet - Spill Kits



# 360 Litre (95 Gallon) Static **Overpack Chemical Spill Kit**

**SK-Y95** 

Spill kit | 360 Litre | Chemical | Static Overpack Absorbency: 360 Litres | 95 US Gallons\*\* Base Fibre: Polypropylene

						The second second second	and the second of the	
Product Code	Colour	Format	Size cm (inches)	<b>Recycled Content</b>	Units/Case	Weight/Case	LTL/Pallet	FTL/Pallet
						(See a		
SK-Y95	Yellow	Spill Kit	N/A	40%*	1	34 kg (75 lbs)	4	4
						J + ··· J (1 J ···· /	- <b>-</b> -	-

#### 360 Litre (95 US Gallon) Static Overpack

The drum container for this spill kit keeps the absorbents clean, dry and ready for use when needed. A large gauge threaded lid and rigid construction allows the drum to be used as an overpack.

This spill kits feature a combination of pads, socks and pillows that will contain and recover a 360 litre spill of hazardous oil-based or

#### Spill kit's contents include:



### 150 x Pads size 38 cm x 46 cm (15" x 18")

The pads in this spill kit are medium weight sonic bonded meltblown polypropylene Chemical. They feature excellent wicking properties and sonic bond points that prevent stray fibres from becoming detached.

# 2 pairs of gloves


Waterproof gloves help to ensure safe handling of spilled substance.

### 20 x Socks size 8 cm x 1.2 m (3" x 4')

These socks feature a spunbond outer sleeve with a durable stitched seam. The core is a next generation absorbent that will recover aggressive and unknown spills. Durable plastic clips seal the sock at both ends.

# 2 pairs of goggles

All-in one clear goggles provide eye protection from splashes.



- Refill 10 pad packs are available for this kit.
- Ensure that disposal of these used sorbents complies with all regulations.

8 x Pillows size 23 cm x 38 cm (9" x 15")

These pillows feature a spunbond outer surface with a super absorbent flake core. This next generation absorbent will absorb and hold large quantities of aggressive, hazardous or unknown fluids.



## 10 x Waste Bags

These are made from a tough grade of polythene. There is also a cable tie supplied so that the waste can be secured safely.

- Basis weights and recycled content are ± 5%
- Measures a case/bale using ASTM 726 (long test) with medium viscosity oil and tap water. Statistical average derived from real time production QC data. \*\*\* Weight per case ± 0.5 kg/lbs.

Compliance	*** Weight per case ± 0.5 kg/lbs.
<b>Related Regulations</b>	Description
29 CFR 1910.120(j)(1)(vii) 29 CFR 1910.120(j)(1)(vii)	
29 CFR 1910.22(a)(2) 40 CFR 263.31	The floor of every workroom shall be maintained in a clean and, so far as possible, a dry condition. Transporters "must clean up any hazardous waste discharge that occurs during transportation.

### **Evolution Sorbent Products Canada Limited**

PDS Date: May, 2015 © Evolution Sorbent Products Canada, Tel: (905) 670 5401 or visit www.espsorbents.com/ca